



# ULTRA SLIM | Track series




Model	Power	Install	Length
1 Meter profile-uls	200W max	Surface/Pendant/Recessed	1000mm
2 Meter profile-uls	200W max	Surface/Pendant/Recessed	2000mm
3 Meter profile-uls	200W max	Surface/Pendant/Recessed	3000mm

Sandy Black
  Sandy White
  Golden
  Black bronze



Model	Power	Install	Length
1 Meter profile-R-uls	200W max	Recessed	1000mm
2 Meter profile-R-uls	200W max	Recessed	2000mm
3 Meter profile-R-uls	200W max	Recessed	3000mm

Sandy Black
  Sandy White
  Golden
  Black bronze



# ULTRA SLIM | Dot series



## Dot12-uls





POWER	CRI	SDCM	CCT	BEAM	LUMINOUS FLUX
12W	> 90 > 80	< 3	3000K 2700K 4000K	25°	1006Lm

Sandy Black
  Sandy White

### LIGHT DISTRIBUTION

3000K 90Ra



## Dot24-uls






POWER	CRI	SDCM	CCT	BEAM	LUMINOUS FLUX
24W	> 90 > 80	< 3	3000K 2700K 4000K	25°	1875Lm

Sandy Black
  Sandy White

### LIGHT DISTRIBUTION

3000K 90Ra





### Linear30-uls





POWER	CRI	SDCM	CCT	BEAM	LUMINOUS FLUX
6W	> 90	< 3	3000K	Diffuse	433Lm
	> 80		2700K		
			4000K		

■ Sandy Black □ Sandy White

#### LIGHT DISTRIBUTION

3000K 90Ra



### Linear50-uls





POWER	CRI	SDCM	CCT	BEAM	LUMINOUS FLUX
12W	> 90	< 3	3000K	Diffuse	890Lm
	> 80		2700K		
			4000K		

■ Sandy Black □ Sandy White

#### LIGHT DISTRIBUTION

3000K 90Ra



### Linear70-uls





POWER	CRI	SDCM	CCT	BEAM	LUMINOUS FLUX
18W	> 90	< 3	3000K	Diffuse	1148Lm
	> 80		2700K		
			4000K		

■ Sandy Black □ Sandy White

#### LIGHT DISTRIBUTION

3000K 90Ra



### Linear90-uls



POWER	CRI	SDCM	CCT	BEAM	LUMINOUS FLUX
24W	> 90	< 3	3000K	Diffuse	1489Lm
	> 80		2700K		
			4000K		

■ Sandy Black □ Sandy White

#### LIGHT DISTRIBUTION

3000K 90Ra

